

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

This Page Blank (uspto)




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G08B 5/22	A1	(11) International Publication Number: WO 96/11454 (43) International Publication Date: 18 April 1996 (18.04.96)
(21) International Application Number: PCT/IB95/00828 (22) International Filing Date: 3 October 1995 (03.10.95) (30) Priority Data: 94202945.5 11 October 1994 (11.10.94) EP (34) Countries for which the regional or international application was filed: NL et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 5, Kista, S-164 85 Stockholm (SE). (72) Inventors: HOFMEESTER, Gerrit, Hendrik; Lijnmarkt 32, NL-3511 KJ Utrecht (NL). KEMP, Johannes, Antonius, Maria; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (74) Agent: GROENENDAAL, Antonius, W., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: CN, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: PAGING RECEIVER**(57) Abstract**

On a paging receiver visual symbols are visually reproduced, relative to one another as in a two-dimensional scene, under the control of a message received.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Paging receiver.

The invention relates to a paging receiver, comprising receiving means for receiving a message, selection means which are arranged to select symbols, in dependence on the message, from a predetermined set of symbols, and reproduction means for the visual reproduction of the selected symbols.

5 A paging receiver of this kind is known from US 5,297,247. Paging receivers are intended for use in a system for dispatching short messages to individual receivers. The paging receiver is capable of visually reproducing a number of predetermined symbols, such as digits, on a display panel. The message determines which symbols are selected for reproduction.

10 The person sending the message transmits its contents to a central station preferably by telephone. If the contents of the message are formed by a row of digits, this row can be transferred by successively selecting a row of digits on the telephone. Verbal contents are usually transferred verbally to an operator who subsequently composes the message by means of an alphanumerical keyboard. This renders the transmission of non-
15 numerical messages expensive and unattractive if very personal messages are concerned. In order to mitigate this drawback, use can be made of code books whereby special meanings can be assigned to series of digits. Information can thus be dispatched by telephone without intervention by an operator.

The use of a code book, however, is not handy and has restrictions.

20 Therefore, it is *inter alia* an object of the invention to provide a paging receiver capable of reproducing a message in such a manner that the users can more readily attach an own meaning thereto, even when short messages are used.

To achieve this, the paging receiver in accordance with the invention is characterized in that the reproduction means are arranged to reproduce visually at least a part
25 of the symbols as pictograms in predetermined locations so as to be situated relative to one another as in a two-dimensional scene. Contrary to digit and/or letter sequences, pictograms arranged as in a scene may have mutually different dimensions and/or be arranged in a non-recurrent pattern of positions. By reproducing the message as a two-dimensional scene, the user is offered a higher degree of freedom of association so that it is easier to agree on and

memorize individual meanings for messages.

Furthermore, it is possible to produce a family of paging receivers whose members deviate from one another in respect of the pictograms and/or the situation of these, pictograms, so that upon reception of one and the same message different members of the
5 family will reproduce different scenes. The user can then select a paging receiver which is suitable for a desired type of meanings.

The sender of the message can readily compose the message by referring to predetermined pictogram symbols. This is desirable notably for paging systems; for example, a scene can be described *via* a telephone dial or keyboard by making a small
10 number of choices, which scene is subsequently dispatched to the paging receiver for reproduction. The number of pictogram symbols is then preferably less than ten, so that each visual symbol corresponds to an own key.

An embodiment of the paging receiver in accordance with the invention is characterized in that the reproduction means comprise a display panel, that each visual
15 symbol of said part corresponds to a predetermined, unique own position on the display panel, regardless of the message, and that the reproduction means are arranged to display each selected visual symbol in its predetermined, unique own position. Because each symbol has its own position in the scene, it is not necessary to transmit position information; moreover, less information suffices to compose the message. Furthermore, in most positions
20 it is then merely necessary to display one symbol or not. Therefore, specially shaped electrodes suffice for the display panel, the shapes of said electrodes corresponding to the pictogram symbols. The pictogram symbols can then also be reproduced on a curved part of the surface of the paging receiver, so that its construction may be more compact. Paging receivers having a facility for the visual display of arbitrary symbols (*i.e.* not only visual
25 pictogram symbols as in a scene) can also be rendered more compact in this manner.

An embodiment of the paging receiver in accordance with the invention is characterized in that the selection means are arranged to detect a predetermined code in the message and to enable selection and reproduction of any one of the visual symbols exclusively upon detection of the code. Thus, the sender can optionally switch on the
30 reproduction of the pictogram symbols in the scene by including the code in the message. If no pictogram symbols need be reproduced, no information for the selection of the pictogram symbols need then be included in the message.

An embodiment of the paging receiver in accordance with the invention is characterized in that the selection means are arranged to detect the presence of given digits in

a series of digits in the message and to select, upon detection, respective visual symbols exclusively associated with said given digits. This offers a simple way of composing the scene for which the sender need remember only little.

An embodiment of the paging receiver in accordance with the invention is
5 characterized in that the reproduction means are arranged to reproduce a row or column of digits and/or letters simultaneously with the visual symbols, and to reproduce therein a digit and/or letter in each reproduction position which is selectable in dependence on the message. Thus, the paging receiver can reproduce, together with the pictogram symbols, for example a telephone number offering supplementary information for the scene. The digits of the
10 telephone number are reproduced in the usual manner, *i.e.* as digits in a row of positions in which an arbitrarily adjustable digit may be present in any position as opposed to the scene configuration of the visual pictogram symbols. In comparison with the digits and/or letters, the scene preferably occupies the major part of the surface of the display panel.

These and further aspects of the invention, its embodiments and
15 advantages will be described in detail hereinafter with reference to Figures. Therein:

Fig. 1 shows a paging system,

Fig. 2 shows a first paging receiver comprising a display panel,

Fig. 3 shows a second paging receiver comprising a display panel, and

Fig. 4 shows a display panel for a paging receiver.

20 Fig. 1 shows a paging system, comprising an input apparatus 10, a central transmitter 12 and a paging receiver 14. The paging receiver 14 comprises a receiving section 140 which is coupled to a first decoder 141 and a second decoder 142, said decoders themselves being coupled to reproduction means 143.

During normal operation, a sender contacts the central transmitter 12, for
25 example *via* a telephone line and subsequently enters a series of digits by way of a keyboard 11 of the input apparatus 10, which digits indicate a specific paging receiver 14 and a specific contents of the message to be dispatched to the paging receiver 14. In response to the code, the central transmitter 12 transmits a message which contains an identification code of the intended paging receiver 14 and the meaningful contents. The receiving section 140 of
30 the paging receiver 14 receives this message and checks whether the identification code in the message corresponds to an internal identification code.

If so, the message is stored in an internal memory (if desired, this memory can be arranged so that more than one message can be simultaneously stored therein so as to be fetched later); the arrival of the message is signalled to the person carrying the

paging receiver, for example by way of a beep. When the person carrying the receiver activates the paging receiver, the receiving section transfers the meaningful contents to the decoders 141, 142; if desired, it is also possible to arrange the paging receiver so that it automatically transfers the meaningful contents, *i.e.* without activation of the receiver by the
5 bearer.

The display means 143 are capable of visually displaying different pictogram symbols from a set of pictogram symbols (to be referred to hereinafter only as symbols for the sake of brevity).

Fig. 2 shows a paging receiver 20, comprising a display panel 22 which
10 forms part of the reproduction means 143. A number of digits 24-1...5 and a number of visual symbols 26a-f are displayed on the display panel.

The first decoder 141 receives the meaningful contents of the message and on the basis thereof it determines which symbols of the set of visual symbols 26a-f are to be displayed and which symbols are not. This is executed on the basis of a series of digits
15 entered by the sender *via* the keyboard 11. For example, a symbol is associated with each digit of the keyboard; for example, a 1 is associated with the visual symbol representing a human being, a 2 with a symbol representing a second human being standing besides the first human being, a 3 with a visual symbol representing a bird, *etc.* The first decoder 141 then determines, on the basis of the message, which digits have been entered *via* the keyboard 11
20 and supplies the reproduction means 143 with a control signal so as to display only the visual symbols associated with these digits. The visual symbols are not arranged in a row relative to one another, but are displayed in a scene. The positions in which the symbols are made visible relative to one another are predefined in the paging receiver, so that these positions need not be indicated in the message.

25 Because the visual symbols do not have a general, predetermined meaning and because the symbols are not arranged in a row but in a scene relative to one another, persons (senders-receivers) utilizing the system can readily attach own meanings to the reproduction of the symbols, it nevertheless being possible to enter the contents of the message by means of a small keyboard, such as a telephone keyboard, by depression of a
30 small number of keys, and to dispatch the message *via* a standard numerical paging system.

The second decoder 142 decodes a part of the message other than the part decoded by the first decoder 141. From the message the second decoder determines a series of digits which have been successively entered *via* the keyboard 11, and supplies the reproduction means 143 with a control signal for reproducing these signals in a row in the

sequence in which they have been entered. The function and the presence of the second decoder are not essential for the use of the paging receiver with the first decoder; however, it is advantageous to supplement the reproduction of the visual symbols by the simultaneous reproduction of digits, for example of a telephone number.

5 In order to enable the two decoders 141, 142 to distinguish the code of the visual symbols from the series of digits, for example, a decoder 141, 142 may be responsive to an opening symbol (for example, entering three digits "0" in direct succession via the keyboard 11), upon reception of which the first decoder 141 is activated and/or to a separation symbol (for example, entering a digit "0" via the keyboard 11) which separates
10 the digits encoding the visual symbols whereto the first decoder responds from the row of digits decoded by the second decoder 142. Evidently, the two decoders 141, 142 may also be constructed as one decoder which has two functions and which is implemented mainly in a data processing unit (not shown) of the paging receiver 14 with appropriate software.

Fig. 3 shows a paging receiver 30 having a cylindrically shaped exterior
15 with a display panel 32 which follows the curvature of the exterior. The exterior of the receiver 30 is thus more effectively used for the panel. For a given surface area of the display panel a smaller and hence better portable receiver thus suffices. For the display panel use can be made of, for example a liquid crystal display whose electrodes are provided on a flexible foil.

20 Fig. 4 shows a display panel comprising two electrode layers 40, 42 wherebetween, for example a liquid crystal material is provided. On at least one of the electrode layers 40 there are arranged electrodes 44, 46, each of which has a shape and location corresponding to a respective symbol to be displayed. By defining the shape and location of the symbols used already in the display panel, the control of the display panel is
25 simplified. If necessary, however, use can also be made of a raster display panel, each symbol then being composed of a number of raster points. To this end, information indicating which raster points must be activated for the display of a given visual symbol can be stored in a ROM (Read-Only Memory) in the paging receiver.

The symbols cannot only be displayed, but also reproduced by means of
30 sound, for example by associating a respective sound signal of a given duration with each symbol; this sound signal is stored in advance in a memory in the paging receiver (or the paging receiver comprises sound-generating means for the respective sound signals). The sounds associated with the selected symbols are then successively reproduced. Alternatively, one or more basic sound signals can be used which can be reproduced by the receiver in a

number of different versions (for example, always the same relative sequence of notes, but alternately fast/slow, with up-transposed pitch/normal, with/without vibrato, with flute/cello *etc.*). The paging receiver then selects one option as a version of the basic signal, in the same way as the selection of the visual symbols, and audibly reproduces the resultant sound
5 signal. The transmitting person and the receiving person can again simply agree to attach their own meaning to the various alternative messages to be audibly reproduced.

The paging receiver can be conceived to reproduce the symbols either as sound or visually. The user can then select the mode of reproduction of the message (visual/audio), for example by means of a switch.

CLAIMS:

1. A paging receiver, comprising receiving means for receiving a message, selection means which are arranged to select symbols, in dependence on the message, from a predetermined set of symbols, and reproduction means for the visual reproduction of the selected symbols, characterized in that the reproduction means are arranged to reproduce
5 visually at least a part of the symbols as pictograms in predetermined locations so as to be situated relative to one another as in a two-dimensional scene.
2. A paging receiver as claimed in Claim 1, characterized in that the reproduction means comprise a display panel, that each visual symbol of said part corresponds to a predetermined, unique own position on the display panel, regardless of the
10 message, and that the reproduction means are arranged to display each selected visual symbol in its predetermined, unique own position.
3. A paging receiver as claimed in Claim 2, characterized in that the reproduction means are arranged to display or not display exclusively the corresponding visual symbol in the own position.
- 15 4. A paging receiver as claimed in Claim 3, characterized in that the display panel comprises, for each symbol of the set, an own control electrode whose shape corresponds to that of the symbol.
5. A paging receiver as claimed in Claim 2, 3 or 4, characterized in that the display panel is curved so as to correspond to a curved enclosure of the paging receiver, the
20 visual symbols being displayed at least partly on a curved part of the surface.
6. A paging receiver as claimed in any one of the Claims 1 to 5, characterized in that the selection means are arranged to detect a predetermined code in the message and to enable selection and reproduction of any one of the visual symbols exclusively upon detection of the code.
- 25 7. A paging receiver as claimed in any one of the Claims 1 to 6, characterized in that the selection means are arranged to detect the presence of given digits in a series of digits in the message and to select, upon detection, respective visual symbols exclusively associated with said given digits.
8. A paging receiver as claimed in any one of the Claims 1 to 7,

characterized in that the reproduction means are arranged to reproduce a row or column of digits and/or letters simultaneously with the visual symbols, and to reproduce therein a digit and/or letter in each reproduction position which is selectable in dependence on the message.

9. A paging receiver as claimed in Claim 8, characterized in that the
- 5 reproduction means comprise a controllable display panel, having a first sub-surface for the visual symbols and a second sub-surface for the row of digits and/or letters, the first sub-surface being larger than the second sub-surface.

1/3




FIG. 1

2/3




FIG. 2

3/3




FIG. 3




FIG. 4

1
INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 95/00828

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: G08B 5/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G08B, H04B, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DIALOG 125,340,350,351

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5087905 A (HIROYASU KURAMATSU ET AL), 11 February 1992 (11.02.92), column 1, line 34 - column 5, line 62, figures 1A-7C, abstract --	1-9
X	WO 9103885 A1 (MOTOROLA INC.), 21 March 1991 (21.03.91), page 1, line 10 - page 7, line 2, figures 1-3, abstract --	1-9
A	CH 681398 A5 (ERIKA KÖCHLER), 15 March 1993 (15.03.93), column 1, line 3 - column 6, line 48, figures 1-6, abstract --	1-9

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

- * Special categories of cited documents:
- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

18 March 1996

21 -03- 1996

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Roland Landström
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 95/00828

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4951039 A (ROBERT J SCHWENDEMAN ET AL), 21 August 1990 (21.08.90), column 1, line 3 - column 10, line 20, figures 1-6c, abstract -----	1-9

INTERNATIONAL SEARCH REPORT
Information on patent family members

05/02/96

International application No.
PCT/IB 95/00828

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 5087905	11/02/92	AU-B- 635539	25/03/93
		AU-A- 5763290	20/12/90
		CA-A,C- 2019153	19/12/90
		DE-D- 69022127	00/00/00
		EP-A,A,A 0404007	27/12/90
		JP-A- 3021124	29/01/91
		KR-B- 9310836	12/11/93
		JP-A- 3022635	31/01/91
WO-A1- 9103885	21/03/91	NONE	
CH-A5- 681398	15/03/93	NONE	
US-A- 4951039	21/08/90	AU-A- 3217489	24/11/89
		CA-A- 1321239	10/08/93
		EP-A,A- 0410978	06/02/91
		WO-A- 8910610	02/11/89